

Identifieringstabell för gängor



Utv. diam (mm)	Inv. diam (mm)	Stigning (gängor/tum)	BSP (cylindrisk)	BSPT (konisk)	NPT	Metrisk (cylindrisk)	Metrisk (konisk)	ORFS / UNF JIC/SAE
7,94	6,79	24,0						5/16"-24
8,00	6,92	25,4				8x1.0		
9,53	8,38	24,0						3/8"-24
9,73	8,57	28,0	1/8"	1/8"				
9,99	8,48	27,0			1/8"			
10,00	8,38	16,9				10x1.5		
10,00	8,70	25,4					10x1.0	
10,00	8,77	25,4				10x1.0		
11,11	9,85	20,0						7/16"-20
11,11	9,85	24,0						7/16"-24
12,00	10,05	16,9					12x1.5	
12,00	10,16	16,9				12x1.5		
12,70	11,45	20,0						1/2"-20
13,16	11,45	19,0	1/4"	1/4"				
13,25	11,00	18,0			1/4"			
14,00	12,05	16,9					14x1.5	
14,00	12,16	16,9				14x1.5		
14,28	12,90	18,0						9/16"-18
15,88	14,35	18,0						5/8"-18
16,00	14,05	16,9					16x1.5	
16,00	14,16	16,9				16x1.5		
16,66	14,95	19,0	3/8"	3/8"				
16,67	14,42	18,0			3/8"			
17,30	16,13	16,0						11/16"-16
18,00	16,05	16,9					18x1.5	
18,00	16,16	16,9				18x1.5		
19,05	17,47	16,0						3/4"-16
20,00	18,05	16,9					20x1.5	
20,00	18,16	16,9				20x1.5		
20,60	19,10	16,0						13/16"-16
20,72	17,81	14,0			1/2"			
20,96	18,63	14,0	1/2"	1/2"				
22,00	20,05	16,9					22x1.5	
22,00	20,16	16,9				22x1.5		
22,22	20,42	14,0						7/8"-14
22,91	20,59	14,0	5/8"					
24,00	22,16	16,9				24x1.5		
25,40	23,11	12,0						1"-12
26,00	24,16	16,9				26x1.5		
26,03	23,13	14,0			3/4"			
26,44	24,12	14,0	3/4"	3/4"				
26,99	24,86	12,0						1.1/16"-12
26,99	24,86	14,0						1.1/16"-14
27,00	24,55	12,7				27x2.0		
27,00	24,55	16,9				27x1.5		
28,58	26,28	12,0						1.1/8"-12
30,00	27,55	12,7				30x2.0		
30,00	28,38	16,9				30x1.5		
30,16	28,04	12,0						1.3/16"-12
30,20	27,88	14,0	7/8"					
31,75	29,46	12,0						1.1/4"-12
32,00	29,84	12,7				32x2.0		
32,59	29,06	11,5			1"			
33,00	30,84	12,7				33x2.0		
33,00	30,55	16,9				33x1.5		
33,25	30,29	11,0	1"	1"				

Identifieringstabell för gängor



Utv. diam (mm)	Inv. diam (mm)	Stigning (gängor/tum)	BSP (cylindrisk)	BSPT (konisk)	NPT	Metrisk (cylindrisk)	Metrisk (konisk)	ORFS / UNF JIC/ SAE
33,34	31,21	12,0						1.5/16"-12
34,93	32,63	12,0						1.3/8"-12
36,00	33,55	12,7				36x2.0		
36,00	34,38	16,9				36x1.5		
37,90	34,94	11,0	1.1/8"					
38,00	36,38	16,9				38x1.5		
38,10	35,81	12,0						1.1/2"-12
41,27	39,14	12,0						1.5/8"-12
41,32	37,78	11,5			1.1/4"			
41,91	38,95	11,0	1.1/4"	1.1/4"				
42,00	39,55	12,7				42x2.0		
42,00	40,38	16,9				42x1.5		
45,00	42,55	12,7				45x2.0		
45,00	43,38					45x1.5		
47,39	43,85	11,5						
47,62	45,49	12,0			1.1/2"			1.7/8"-12
47,80	44,85	11,0	1.1/2"	1.1/2"				
48,00	45,55	12,7				48x2.0		
52,00	49,55	12,7				52x2.0		
52,00	50,38	16,9				52x1.5		
53,75	50,79	11,0	1.3/4"					
59,60	56,70	11,5			2"			
59,61	56,66	12,0	2"					

Förkortningar

API = American Petroleum Institute Taper Thread
 ASAE = American Society of Agricultural Engineers
 ASSPT = American National Straight Pipe Thread
 BSP = British Standard Pipe Thread
 (SE: Rörgänga)
 BSPT = British Standard Pipe Tapered Thread
 (SE: Konisk rörgänga)
 DIN = Deutsche Institut für Normung
 FIEI = Farm Industrial Equipment Institute
 FPT = Female Pipe Thread
 GHT = Garden Hose Threads
 IPT = American Iron Pipe Thread – Straight
 JIC = Joint Industri Conference (SAE 37)
 JIS = Japanese Industrial Standard
 M = Metric Thread
 MM = Metric Thread

NPS = American National Pipe Thread – Straight
 NPSM = American National Pipe Thread
 – Straight Mechanical
 NPT = American National Pipe Thread – Taper
 NPTF = American National Pipe Thread – Taper (Dry seal)
 NST = American National Standard Thread – Straight
 ORSF = O-Ring Face Seal fitting (ISO 8434-3)
 R = Rörgänga (BSP)
 RT = British Round Thread
 SAE = Society of Automotive Engineers
 URT = Dennis Urban Round Thread
 UNC = Unified Coarse Thread
 UNF = Unified Fine Thread
 UNS = Unified National Special
 VEE = Shelvoke Drewry "VEE" Round Thread
 W = Withworth Thread