

Gevindtabel



Udvendig mål	Indvendig mål	Gevind	BSPP	BSPT	NPT/S	Metrisk	Metrisk	ORFS / UNF JIC / SAE
mm	mm		cylindrisk	konisk		cylindrisk	konisk	
7,94	6,79	24.0						5/16"-24
8,00	6,92	× 1.0				8 × 1.0		
9,53	8,38	24.0						3/8"-24
9,73	8,57	28.0	1/8"	1/8"				
9,99	8,48	27.0			1/8"			
10,00	8,38	× 1.5				10 × 1.5		
10,00	8,70	× 1.0					10 × 1.0	
10,00	8,77	× 1.0				10 × 1.0		
11,11	9,85	20.0						7/16"-20
11,11	9,85	24.0						7/16"-24
12,00	10,05	× 1.5					12 × 1.5	
12,00	10,16	× 1.5				12 × 1.5		
12,70	11,45	20.0						1/2"-20
13,16	11,45	19.0	1/4"	1/4"				
13,25	11,00	18.0			1/4"			
14,00	12,05	× 1.5					14 × 1.5	
14,00	12,16	× 1.5				14 × 1.5		
14,28	12,90	18.0						9/16"-18
15,88	14,35	18.0						5/8"-18
16,00	14,05	× 1.5					16 × 1.5	
16,00	14,16	× 1.5				16 × 1.5		
16,66	14,95	19.0	3/8"	3/8"				
16,67	14,42	18.0			3/8"			
17,30	16,13	16.0						11/16"-16
18,00	16,05	× 1.5					18 × 1.5	
18,00	16,16	× 1.5				18 × 1.5		
19,05	17,47	16.0						3/4"-16
20,00	18,05	× 1.5					20 × 1.5	
20,00	18,16	× 1.5				20 × 1.5		
20,60	19,10	16.0						13/16"-16
20,72	17,81	14.0			1/2"			
20,96	18,63	14.0	1/2"	1/2"				
22,00	20,05	× 1.5					22 × 1.5	
22,00	20,16	× 1.5				22 × 1.5		
22,22	20,42	14.0						7/8"-14
22,91	20,59	14.0	5/8"					
24,00	22,16	× 1.5				24 × 1.5		
25,40	23,11	12.0						1"-12
26,00	24,16	× 1.5				26 × 1.5		
26,03	23,13	14.0			3/4"			

Udvendig mål	Indvendig mål	Gevind	BSPP	BSPT	NPT/S	Metrisk	Metrisk	ORFS / UNF JIC / SAE
mm	mm		cylindrisk	konisk		cylindrisk	konisk	
26,44	24,12	14.0	3/4"	3/4"				
26,99	24,86	12.0						1.1/16"-12
26,99	24,86	14.0						1.1/16"-14
27,00	24,55	× 2.0				27 × 2.0		
27,00	24,55	× 1.5				27 × 1.5		
28,58	26,28	12.0						1.1/8"-12
30,00	27,55	× 2.0				30 × 2.0		
30,00	28,38	× 1.5				30 × 1.5		
30,16	28,04	12.0						1.3/16"-12
30,20	27,88	14.0	7/8"					
31,75	29,46	12.0						1.1/4"-12
32,00	29,84	× 2.0				32 × 2.0		
32,59	29,06	11.5			1"			
33,00	30,84	× 2.0				33 × 2.0		
33,00	30,55	× 1.5				33 × 1.5		
33,25	30,29	11.0	1"	1"				
33,34	31,21	12.0						1.5/16"-12
34,93	32,63	12.0						1.3/8"-12
36,00	33,55	× 2.0				36 × 2.0		
36,00	34,38	× 1.5				36 × 1.5		
36,51	34,50	12.0						1.7/16"-12
37,90	34,94	11.0	1.1/8"					
38,00	36,38	× 1.5				38 × 1.5		
38,10	35,81	12.0						1.1/2"-12
41,27	39,14	12.0						1.5/8"-12
41,32	37,78	11.5			1.1/4"			
41,91	38,95	11.0	1.1/4"	1.1/4"				
42,00	39,55	× 2.0				42 × 2.0		
42,00	40,38	× 1.5				42 × 1.5		
42,86	40,70	12.0						1.11/16"-12
45,00	42,55	× 2.0				45 × 2.0		
45,00	43,38	× 1.5				45 × 1.5		
47,39	43,85	11.5						
47,62	45,49	12.0			1.1/2"			1.7/8"-12
47,80	44,85	11.0	1.1/2"	1.1/2"				
48,00	45,55	× 2.0				48 × 2.0		
52,00	49,55	× 2.0				52 × 2.0		
52,00	50,38	× 1.5				52 × 1.5		
53,75	50,79	11.0	1.3/4"					
59,60	56,70	11.5			2"			
59,61	56,66	12.0	2"					

Forkortelser

BSPP British Standard Pipe Thread (Rørgevind)

BSPT British Standard Pipe Tapered Thread
(Konisk rørgevind)

DIN Deutsche Institut für Normung

JIC Joint Industri Conference (SAE 37)

JIS Japanese Industrial Standard

M Metric Thread

NPTF American National Pipe Thread – Taper (Dry seal)

ORFS O-Ring Face Seal fitting (ISO 8434-3)

SAE Society of Automotive Engineers

UNF Unified Fine Thread