

Puristusmittataulukko

Gates/IMM 1-, 2- ja 4-vahvisteiset

LETKUTYYPPI	Koko	03	04	05	06	08	10	12	16	20	24	32
	Tuumaa	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"
G1 	Holkki 1C4010 Ei kuorita		1C-04	1C-05	1C-06	1C-08	1C-10	1C-12	1C-16			
			15,7	18,2	19,3	23,0	26,8	30,2	38,7			
	Holkki 1P4010	1P-03	1P-04	1P-05	1P-06	1P-08	1P-10	1P-12	1P-16	1P-20	1P-24	1P-32
		14,9	16,5	19,0	21,0	25,0	28,2	31,8	39,5	47,4	53,0	65,5
	Kuorittava	22	22	22	24	25	27	31	37	43	45	61
G2 	Holkki 3P4010 Ei kuorita		3P-04	3P-05	3P-06	3P-08	3P-10	3P-12	3P-16	3P-20	3P-24	3P-32
			17,2	19,3	20,5	24,9	28,5	32,6	40,8	51,0	58,0	71,0
	Holkki 2P4010 /2PT		2P-04	2P-05	2P-06	2P-08	2P-10	2P-12	2PT-16	2PT-20	2PT-24	2PT-32
			18,0	21,1	22,4	25,7	29,0	33,0	41,0	49,5	57,5	70,0
	Kuorittava		22	22	24	25	27	31	37	43	45	61
M2T 	Holkki 3P4010 Ei kuorita		3P-04		3P-06	3P-08	3P-10	3P-12	3P-16	3P-20	3P-24	3P-32
			16,8		20,1	24,2	28,0	31,5	39,1			
M3K 	Holkki 1C/3P4010 Ei kuorita	1C-03	1C-04		1C-06	1C-08	3P-10	3P-12	3P-16			
		13,5	15,1		19,6	22,8	28,7	31,6	40,7			
M4K 	Holkki 3P4010 Ei kuorita				3P-06	3P-08	3P-10	3P-12				
					20,4	24,4	28,4	31,7				
M5K 	Holkki 3P4010 Ei kuorita		3P-04	3P-05	3P-06	3P-08						
			16,5	19,0	20,0	24,3						
EFG3K 	Holkki 9P4010									9P-20	9P-24	
										50,1	59,0	
	Kuorittava									54	62	
EFG4K 	Holkki 9P4010					9P-08	9P-10	9P-12	9P-16			
						26,2	30,1	33,9	41,8			
	Kuorittava					28	27	32	47			
EFG5K 	Holkki 9P4010				9P-06	9P-08	9P-10	9P-12	9P-16			
					22,3	26,3	30,0	34,0	42,7			
	Kuorittava				25	29	31	48				

HOLKIN
TYYPPI

PURISTUS-
MITTA

KUORINTAPITUUS

Arvot ovat ohjeellisia. Virheettömän tuloksen takaamiseksi on syytä mitata liittimen reiän supistuma tulkkisarjan avulla.